

ADDING CHIMNEY SECTIONS:

Add chimney sections as required locking securely in place to the required height. The top of the chimney will extend at least 3 feet above the point where it comes through the roof and at least 2 feet above any surface or structure within a horizontal distance of 10 feet. (SEE FIG. 13)

INSTALLING FLASHING:

Place the proper flashing over chimney pipe and mark outline on roof. Remove nails from shingles in this outline to bottom edge of roof cutout. (SEE FIG.15). Coat area on roof with roof cement. Slide flashing under shingles into position and re nail top and side shingles. DO NOT NAIL through lower portion of flashing. If necessary cover side and top of flashing with salvaged shingles.

INSTALLING STORM COLLAR:

Install storm collar and raise upward (SEE FIG. 16). Apply waterproof caulking around chimney 1" above top of flashing and push storm collar down into caulking and tighten in place.

RAIN CAP:

***IMPORTANT:** Chimney outlet must be at least 3 feet above roof. It must also be at least 2 feet above the highest point of the roof within 10 feet in a horizontal plane.
Ice rain cap on top chimney section and lock with a clock - wise twist.

FINISHING:

Apply finishing materials to framing making sure that combustible materials do not cover fireplace facing. Non-combustible materials may be used on fireplace if desired.

***NOTE:** If the fireplace is being recessed into an outside wall the entire enclosure must be completely insulated (floor, walls, and ceiling including vapour barrier) to avoid transfer of cold air through the fireplace when not in use.

***NOTE:** THE SIDES AND THE BACK OF THE FIRE BOX IS TO BE INSTALLED ONLY AGAINST A FINISHED (SURFACE) WALL. NOT AGAINST A VAPOUR BARRIER OR EXPOSED INSULATION.

WARNING: Any deviation from these installation instructions as it relates to clearances, protection of combustible materials or the use of UIC labelled parts shall nullify the manufacturers warranties and may VOID the U.I.C. Label.

IMPORTANT NOTICE: MODEL "SSG" CHIMNEYS ARE AVAILABLE IN CHOICE OF GALVANIZED AND STAINLESS STEEL OUTER CASINGS, HOWEVER THE MANUFACTURER RECOMMENDS AND WARRANTS ONLY STAINLESS STEEL CLAD LENGTHS FOR EXTERIOR USE.

